

# 24-Port 10/100BaseTX + 2 Gigabit Slots Layer 2 SNMP Stackable Switch



## Overview

The CS-GR3280 is a Layer 2 switch with powerful network management function and flexible connectivity combination of 24 10/100 Mbps ports and two optional Gigabit modules; CS-GM1100 is a 1-port Gigabit over copper 1000Base-TX module and FM1100 is a 1-port Gigabit over Fibre 1000Base-SX module. Strictly adhering to network standards, CS-GR3280 easily fits in your current network configuration, executing the management tasks. Diversified management access windows, user friendly interface, Console, Telnet, and WEB, facilitate the administrators job, reducing management effort to a minimum.

Also, the SNMP (Simple Network Management Protocol), CS-GR3280 lets administrators easily manage and monitor the network, ensuring efficiency of installation and maintenance. Moreover, its support of up to 8 switches stacking facilitates users to utilize the equipment with less cost and more convenience along with QoS and VLAN functions which make the network management easier.

## Environments

Operating Temp.	0°C to 40°C (32°F to 104°F)
Storage Temp.	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	20% to 85%, relative humidity, non-condensing
Storage Humidity	20% to 90%, relative humidity, non-condensing

## Ordering information

CS-GR3280	24-Port 100BaseTX + 2 Gigabit Slots Layer 2 SNMP Stackable Switch
CS-GM1100	1-port 1000Base-T Copper Module, 100 Meters
CS-FM1100	1-port 1000Base-SX Fibre Module, 220/550(Meters)
CS-FM1030	1-port 1000Base-LX Fibre Module, 550 M/10 KM
CS-FM1120	1-port 100BaseFX Fibre Module, ST connector, 2 KM
CS-FM1121	1-port 100BaseFX Fibre Module, SC connector, 2 KM



## Benefits

• Idea to ISP/ASP to charge customers via the Rate Limit flow control.

